



D R I V E

Model 2040

GENERAL DIMENSIONS

Height range (to litter top)		
High	30.5"	(77.5 cm)
Low	17.0"	(43.2 cm)
Caster diameter		
Standard	6.0"	(15.2 cm)
Litter positioning		
Head section	0° - 90° (siderails must be down or intermediate position)	
Knee gatch	0° - 35°	
Trend./reverse Trend.	+10°/-12°	
Maximum weight capacity	500 lbs	(227 kg)
Patient surface	35.0" x 84.0"	(88.9 x 213.4 cm)
Frame length	93.0"	(236.2 cm)
Frame width (siderails up)	42.5"	(108.0 cm)
Frame width (siderails down)	36.0"	(91.4 cm)

Stryker reserves the right to change specifications without notice.



STANDARD FEATURES

- ▶ ZOOM Drive System
- ▶ Battery back-up motion controls
- ▶ Patient positioning package
 - cardiac chair, emergency drop
 - siderail and footboard controls
 - high/low, Trend./reverse Trend.
- ▶ Head-end motion control panel
- ▶ Articulating, zero-transfer gap, split siderails
- ▶ Scale-isolated, head-end IV poles and foley hooks
- ▶ Side-activated, four-wheel ring brake system
- ▶ 90° head section for upright chest imaging
- ▶ Fluoroscopic capable litter – neck through pelvis
- ▶ 6" (15.2 cm) casters
- ▶ Footboard motion lock-out and up/down controls
- ▶ Manual leg-lift prop for quick Trendelenburg and housekeeping
- ▶ Integrated 8" (20.3 cm) frame extender (does not include pad)
- ▶ Removable headboard with integrated CPR board
- ▶ Convenient five-point patient restraint strap anchors
- ▶ Chart rack

OPTIONAL FEATURES

- ▶ Scale system
- ▶ Chaperone™ center-of-gravity bed exit system
- ▶ Mattresses
 - IsoFlex™ Isolibrum™ Pressure Management
 - REM pressure reducing series
 - Aires pressure relieving air cushion support
- ▶ IV poles
 - permanently attached two-stage Infusion II™ folding IV pole
 - removable IV pole
- ▶ Head section/X-ray cassette holder
- ▶ Defibrillator tray
- ▶ Upright oxygen bottle holder
- ▶ Siderail transducer mount
- ▶ IV pole transducer mount
- ▶ Frame extender pad
- ▶ Patient control pendant
- ▶ Pillow speaker interface port(s)
- ▶ Patient restraints
- ▶ Siderail communications
 - nurse call, TV, radio, volume, lights, speaker

ELECTRONICS

- ▶ Electronics UL listed (UL 2601)
- ▶ Volts 115 VAC
24 VDC (ZOOM Drive)
- ▶ Ampere rating 7 amps
- ▶ Current leakage <100 microamperes
- ▶ Frequency 60 Hz
- ▶ Hospital grade plug Yes

